

TL30

ALPHA LITE LED Track Light Data Sheet

Fixture Information

- Angle adjustable
- High color rendering of CRI 90 or higher
- COB LED Chip
- All-in-one Main drive controller
- RDM network communication possible
- Maintain the last signal when DMX signal is lost
- Dimming curve selectable (Linear & curve dimming)

Optional Accessories



4 leaf barndoor



Diffuser



Honeycomb

CRI
95°

High CRI
True Color

TCRI
95°

High TLCI
True Color



Flicker Free




Long LED
Lifetime



Specifications

| | |
|--|--------------------------------|
| LED Chip Type | 32W |
| Estimated LED Lifetime (hours) | 50,000 |
| White Light (K) | 5600 |
| Color Rendition (%) | 97 |
| (Optional) Dimming with Controller (%) | 0-100 [Option] with Controller |
| Beam Angle (°) | 30 / 40 / 60 |
| Signal Control | 6 way Track rail DMX |
| (Optional) Individual Control | [Option] Dip Switch |
| (Optional) Supported Protocol | DMX512 with Controller |
| Remote Device Management | Not Supported |
| Channel Function | Dimming |
| Track Adapter | 2-way / 4-way / [Option] 6-way |
| Power Input Voltage | AC 200-240V |
| Power Consumption (W) | 28.8 |
| Body Dimensions (mm/inch) (DIA x L) | ø99 x 150 |
| Body Weight (kg/lbs) | 1.5 / 3.3 |

Dimension



(Optional) LED Track Light Controller



WWW.ALPHA-LITE.NET

