

Great Flatness

CYC500

ALPHA LITE LED Cyclorama / Horizont Light Data Sheet

Fixture Information

- · Evenly distributes the horizont over 8m
- · Based on 6 colors of R, G, B, W, Amber + primary color to pastel tone
- · Support RDM network communication, and DMX signal check and error message can be
- · Operate Hue & Saturation function for color direction by using Smart Touch Screen
- replaced through the MASTER SLAVE function.
- · Long life, reduce maintenance costs and

Optional Accessories





Pole operation yoke



Power cable



DMX cable





Lighting Quality







USB Firmware Upgrade



Long LED Lifetime



Great Flat Brightness










Specifications

LED Chip Type	3W CREE XP-E x 108ea
Estimated LED Lifetime (hours)	50,000
Full Color Light	Full Red + Green + Blue + Amber + White + Royal blue
Color Rendition (%)	CRI 90-94 / TLCI 89
Dimming (%)	0~100 (16-bit)
Light Aperture Size (mm/inch)	450 x 115 / 17.7 x 4.5
Beam Angle (*)	Asymmetric [60x135° / 85x150° / 130x60° / 20x60° / 30x60° / 40x60°]
Signal Control	5-Pin DMX In and Out
Individual Control	Smart Touch LCD Controller
Supported Protocol	DMX512 / RDM
(Optional) Supported Protocol	DMX512 Wireless / RDM Wireless
Remote DeviceManagement	Supported
Channel Function	Dimming / RGBAWRB / Color Macro / Strobe
Power Input Voltage	AC 100-240V / 50~60Hz
Power Consumption (W)	300
Ambient Temperature Operation (°C)	-20~45
Body Dimensions (mm/inch) (WHD)	556 x 193 x 186 / 21.9 x 7.6 x 7.3
Full Dimensions with Manual Yoke (mm/inch) (WHD)	664 x 251 x 203 / 26.1 x 9.9 x 8
Body Weight (kg/lbs)	8.6 / 19
Full Weight with Manual Yoke (kg/lbs)	9.4 / 20.7
Protection Class	IP20

Dimension








Light Distribution

► (W)6m x (H)8m



WWW.ALPHA-LITE.NET







